

DESCRIPTION

Nautix P1 primer is used to improve the adhesion of paint on GRP surface : new and clean GRP surface or bare GRP. Very easy application : Nautix P 1 is a one-pot primer and one coat is enough.

COMPOSITION

Vinylic resin. Colour : grey. Finish : gloss. Solvent : acetatebuthyl, MIBK

WORKERS PROTECTION

Work in a well ventilated area, wear suitable protective clothing, gloves and eye/face protection.

PREPARATION

Wash the hull with fresh water and detergent. Apply with a clean non fluffy cloth, Degreaser Nautix SD, and dull. Before application support must be clean and dry. Any loose paint must be removed.

APPLICATION

Shake and stir thoroughly before use. Do not apply under 10°C. Application methods: brush, roller, spray gun. Number of coat: 1 Thinner - Cleaner: Nautix DP - Maximum dilution : 10 % Recommended wet coat thickness per coat : 80 microns.

DRYING TIME

Temperature	10°C	15°C	20°C	35°C
Touch dry/overcoating	4 H	3 H	2 H	1 H
End dry	8 H	6 H	4 H	2 H

TECHNICAL DATA

Pack sizes : 0,75 Ltr - 2,5 Ltr - 20 Ltr. Product weight Kg/Ltr : 1,1 +/-0,05. Volume solids : 34 % +/- 3. Coverage : 13 m^2 /Ltr. Flash point : 20°C

NAUTIX P1

SAFETY DATA

R 10	Flammable.
R 20	Harmful by inhalation.
R 48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R 52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R 63	Possible risk of harm to the unborn child.
~ ~	

- S 2 S 36/37 Keep out of the reach of children.
- Wear suitable protective clothing and gloves. If swallowed, seek medical advice immediately and show this container or label. S 46

Emergency phone number : +33 (0)1 45 42 59 59

NAUTIX SA Z.I des 5 chemins 56520 GUIDEL FRANCE Fax : + 33 (0)2 97 65 03 54 Tel : + 33 (0)2 97 65 32 69 E.mail : info@nautix.com www.nautix.com